

---

## **PRODUCT DESCRIPTION**

P-301 is effective on a wide range of crude oils. It prevents the formation of solid tank bottoms. It will help keep the crude in a liquid form during cold weather operations. P-301 is most effective on dark paraffinic crudes.

---

## **RECOMMENDED APPLICATION**

P-301 is injected continuously at the wellhead or down the annulus via a side stream flush system for removal and inhibition of paraffin from downhole. Recommended treating rate is 100 to 2000 ppm. Stimulation treatments may require 3 to 5 gallons of chemical per 1000 gallons of fluid to be treated.

---

## **COMPATIBILITY**

P-301 is incompatible with water in the container. There is no compatibility problem with produced water in the system.

---

## **TYPICAL PHYSICAL PROPERTIES**

Form:	Liquid
Chemical Family:	Polymer in Solvent
Color:	Yellow
Solubility:	Oil
Odor:	Aromatic
Wt. per Gal.:	7.31 lbs.
Charge:	NA
Flash Point:	130 <sup>0</sup> F (54.5°C)

---

## **HANDLING/STORAGE**

P-301 is a flammable liquid. Keep away from heat, sparks, open flames, and any ignition source. Refer to the Material Safety Data Sheet (MSDS) for handling and hazard data.

---

## **PACKAGING**

P-301 is available in 55 gallon metal drums and metal totes.