
PRODUCT DESCRIPTION

PP-300 is a dark amber liquid used to inhibit the formation of and remove deposits of paraffin from oil wells, pipelines and related equipment and as a stimulation fluid additive to protect against paraffin problems.

RECOMMENDED APPLICATION

PP-300 is normally continuously injected at the wellhead or down the annulus for removal and inhibition of paraffin deposits in a pipeline or down-hole tubulars normally at 100 - 1000 ppm of total produced hydrocarbons. For use with stimulation treatments 2 to 3 gallons per 1000 gallons of treating fluid will prevent paraffin problems during the well clean up period and normally for some production period thereafter. Placing the PP-300 in the pre pad of fracturing treatments or leading volume of acid treatments is recommended. Routine treatment of the well with PP-300 can then be done to continue the protection against paraffin deposit formation.

COMPATIBILITY

PP-300 is incompatible with water in container. No incompatibility with produced water in system.

Recommendation of the best product for treatment can be made after survey by sales personnel.

TYPICAL PHYSICAL PROPERTIES

Form:	Liquid
Chemical Family:	Organic
Color:	Amber
Solubility:	Oil
Odor:	Pungent
Wt. per Gal.:	7.25 lbs.
Charge:	NA
Flash Point:	61 ⁰ F (16.1°C)

HANDLING/STORAGE

PP-300 is a flammable liquid! Keep away from heat, sparks, open flames and any ignition source. Refer to the Material Safety Data Sheet (MSDS) for handling and hazard data.

PACKAGING

PP-300 is shipped in 55 gallon poly drums.