
PRODUCT DESCRIPTION

TB-701 was originally formulated as a tank bottom treating chemical. It is used extensively to clean up producing wells downhole as well as clean out the production string, flowline. TB-701 will carry on to the tanks to aid in the clean up of tank bottoms. TB-701 is effective on paraffin and asphaltene based crudes.

RECOMMENDED APPLICATION

TB-701 is usually injected continuously at the wellhead flowline to allow for maximum mixing of the product with the produced fluid. TB-701 is normally batched into the tank of bad oil, then rolled with a gas line to mix the fluid with the chemical.

COMPATIBILITY

TB-701 is hydrocarbon based and should not have any water in the container. It is compatible with the produced water in the system.

TYPICAL PHYSICAL PROPERTIES

Form:	Liquid
Chemical Family:	Surfactant/Solvent
Color:	Dark amber
Solubility:	Oils
Odor:	Mild solvent
Wt. per Gal.:	7.30 lbs.
Flash Point:	70° F (21.1°C)

HANDLING/STORAGE

TB-701 is a flammable liquid. Keep away from heat, sparks, open flames and any ignition source. Refer to Material Safety Data Sheet (MSDS) for handling and hazard data.

PACKAGING

TB-701 is available in 55 gallon metal drums.